

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HMIS^a

HEALTH	3	REACTIVITY	0
FLAMMABILITY	2	PERSONAL PROTECTION	B

Identity (As Used on Label and List)

07816, 07820

Graffiti & Spray Paint Remover

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

SECTION I

Manufacturer's Name

ITW Dymon

Emergency Telephone Number

1-800-535-5053

Address (Number, Street, City, State, and ZIP Code)

805 East Old 56 Highway

Telephone Number for Information

1-913-397-9889

Olathe, Kansas 66061

Date Prepared

January 6, 2005

Signature of Preparer (Optional)

Regulatory Dept.

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific

Chemical Identity, Common Name(s))

CAS No.

OSHA PEL

ACGIH-TLV

Other Limits

Recommended

% (Opt.)

Acetone	67-64-1	1000 ppm	500 ppm	STEL 750 ppm	1 - 5 %
*Butoxyethanol (skin designation)	111-76-2	50 ppm	20 ppm		5 - 10 %
Isobutane	75-28-5	800 ppm	800 ppm		15 - 40 %
Propane	74-98-6	1000 ppm	Asphyxiant		3 - 7 %
*Toluene	108-88-3	200 ppm	50 ppm	STEL 150 ppm	20 - 35 %

* This product contains 2-Butoxyethanol (a glycol ether compound) and Toluene that are listed and may require reporting under SARA Title III Sec. 313 if used over the threshold reporting quantity. This information must be included in all MSDSs that are copied and distributed for this material.

TSCA: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

SECTION III Physical/Chemical Characteristics

Boiling Point Concentrate - initial	220° F	Specific Gravity (H₂O = 1) Concentrate	0.943
Pressure (psig. @ 70° F)	40 ± 5	Melting Point	No Data
Vapor Density (AIR = 1)	Greater than one (1)	Evaporation Rate (Ethyl Ether = 1)	No Data
Solubility in Water Complete		pH	12.5 ± 0.5
Appearance and Odor --Opaque white to light tan emulsion with an aromatic odor in an aerosol can.		VOC's --This product contains 457.5 grams per liter or 60.5 % by weight VOC's.	

SECTION IV - Fire and Explosion Hazard Data

USA Flame Projection Test Greater than 18", no flashback, Flammable	Flammable Limits No Data	LEL No Data	UEL No Data
---	------------------------------------	-----------------------	-----------------------

Extinguishing Media -

Carbon dioxide, dry chemical, foam.

Special Fire Fighting Procedures -

Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

Unusual Fire and Explosion Hazards -

Aerosol container (pressurized) may burst if heated over 120° F. Flammable contents.

SECTION V - Reactivity Data

Stability	Unstable		Conditions to Avoid - Extreme heat, direct sunlight
	Stable	X	
Incompatibility (Materials to Avoid) - Strong acids and oxidizers, chlorinated compounds and select amines.			
Hazardous Decomposition or Byproducts - Oxides of carbon, smoke, soot.			
Hazardous Polymerization	May Occur		Conditions to Avoid - None known
	Will Not Occur	X	

SECTION VI - Health Hazard Data

Route(s) of Entry	Eyes? Yes	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) - Danger. Flammable liquid and vapor. Corrosive. Causes eye and skin burns. May be harmful or fatal if swallowed. May cause respiratory tract irritation. May be absorbed through intact skin. Repeated or prolonged occupational overexposure can cause dermatitis and Painter's syndrome.				
Carcinogenicity: None known	NTP? No	IARC Monographs? No	OSHA Regulated? No	

WARNING: This product contains a chemical (Toluene) known to the State of California to cause birth defects or other reproductive harm.

Signs and Symptoms of Exposure - Redness, burning, drying of skin. Drowsiness, dizziness, loss of coordination, fatigue. Slick feeling on skin. Redness, burning and tearing in eyes.

Medical Conditions Generally Aggravated by Exposure - Pre-existing skin and lung disorders. Overexposure may also aggravate pre-existing blood, liver and kidney disorders.

Emergency and First Aid Procedures:

Eyes - Flush with plenty of water for at least 15 minutes. Get medical attention immediately. **Ingestion** - Call a physician immediately. ONLY induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. **Inhalation** - Get to fresh air. If breathing has stopped, qualified personnel should administer artificial respiration. **Skin** - Flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.

SECTION VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled - Wipe up small spills with an absorbent material. For large spills, isolate traffic and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread. Pick up on an absorbent material and put in suitable container for proper disposal. Caution, slip and fall hazard.

Waste Disposal Method - Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard container if allowed by applicable statutes.

Precautions to be Taken in Handling and Storing - Corrosive. Do not get in eyes, on skin or clothing. Do not use around ignition sources such as heat, sparks, open flame, etc. Do not swallow. Do not inhale mist or vapors. Use with adequate ventilation.

Other Precautions - Keep out of reach of children. Contents under pressure. Do not puncture or incinerate container. Store in a cool (under 120° F) dry location away from heat, sparks, open flame or direct sunlight. Direct spray away from face. Replace cap when not in use. Do not deliberately concentrate and inhale vapors. Do not smoke while using.

SECTION VIII - Control Measures

Respiratory Protection (Specify Type) - Not usually necessary. Use with adequate ventilation. If PELs or TLVs are exceeded (see Section II), use an approved NIOSH/MSHA respirator.

Ventilation	Local Exhaust - Not usually necessary	Special - None
	Mechanical (General) - Yes	Other - None
Protective Gloves - Yes (impervious)	Eye Protection - Yes (goggles or approved safety glasses)	

Other Protective Clothing or Equipment

Only as needed to prevent direct contact (i.e., apron, boots, face shield, etc.)

Work/Hygienic Practices

Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc.

WARNING: The use of this product is beyond the control of the manufacturer; therefore, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The user must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials. The manufacturer warrants only that this product meets the manufacturer's specifications for such product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE IMPROPER USE OF THIS PRODUCT. The sole and exclusive remedy against the manufacturer for breach of warranty shall be reimbursement of the purchase price of the product in the event that a defective condition of the product shall be found to exist. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.