

MATERIAL SAFETY DATA SHEET

SECTION ONE - GENERAL INFORMATION Date Revised: 01/07

PRIMARY TRADE NAME:

Unbelievable!® UN GOO®

GENERIC DESCRIPTION:

Grease, Oil, Tar and Adhesive Remover

MANUFACTURER'S NAME AND ADDRESS:

CORE PRODUCTS CO., INC.

401 INDUSTRIAL DR.

CANTON, TX 75103

Health - 2

Flammability - 1

Reactivity - 0

Speical - 0

Rating Scale

0 – Minimal 1 – slight 2 - moderate
3 – serious 4 - severe

EMERGENCY TELEPHONE NUMBER: **Chemtrec 1-800-424-9300**

TELEPHONE NUMBER FOR INFORMATION: **1-800-825-2673**

SECTION TWO - HAZARDOUS INGREDIENTS/HEALTH HAZARD DATA

This product has not been tested as a whole for health effects on animals or humans. This product HAS been tested as a whole for flammability and combustibility and is COMBUSTIBLE as a whole as defined in 29 CFR 1910.1200. Ingredients with a PEL or which present hazards other than combustibility are:

<u>INGREDIENTS:</u>	<u>CAS#</u>	<u>%</u>	<u>PEL</u>	<u>TLV</u>	<u>SARA III</u>
Perchloroethylene	127-18-4	10 - 35	25 ppm	25 ppm	Yes
Petroleum Distillates	8052-41-3	55 - 75	500 ppm	100 ppm	

SECTION THREE - PHYSICAL DATA

BOILING POINT (F): > 300°F (> 149°C)

pH: Not Applicable

VAPOR PRESSURE (mm/Hg): ND

SP. GRAVITY (WATER=1) 0.99-1.01

VAPOR DENSITY (AIR=1):>1

SOLUBILITY IN WATER: Insoluble

EVAPORATION RATE (ETHYL ETHER=1) <1

APPEARANCE AND ODOR: Clear to pale yellow liquid with citrus odor. Natural ingredient content may cause color to vary.

SECTION FOUR - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD):

AUTONITION TEMPERATURE:

LEL:

UEL:

>150 F TCC

ND

ND

ND

EXTINGUISHING MEDIA: Foam, Co2, Dry Chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Use niosh approved self-contained breathing apparatus and full protective equipment (fp n). Use water spray to keep containers cool during fire situations

UNUSUAL FIRE AND EXPLOSION HAZARDS: UFC/OSHA Class II combustible liquid.
High concentrations of vapor can travel distances to ignition source and flash back.

SECTION FIVE - HEALTH HAZARD DATA

CARCINOGENICITY: Perchloroethylene 127-18-4 State of California Proposition 65

PRIMARY ROUTE OF ENTRY: Eyes, Skin, Inhalation and Ingestion

SYMPTOMS OF HEAVY ACUTE AND/OR PROLONGED EXPOSURE:

Product contact with eyes will cause irritation. Prolonged or repeated exposure will irritate the skin. Harmful if chronically inhaled. Harmful if swallowed. Aspiration of material into lungs can cause chemical pneumonitis.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Dermatitis and respiratory disorders

EMERGENCY FIRST AID:

EYES: Flush with plenty of water while lifting eyelids for 15 minutes. If irritation persists, call a physician.

SKIN: Wash with soap and water. If irritation occurs, seek medical attention.

INGESTION: do not induce vomiting; get immediate medical attention.

INHALATION: Remove to fresh air, if problem breathing, seek medical attention.

SECTION SIX - REACTIVITY DATA

STABILITY: Stable.

CONDITIONS TO AVOID: None

INCOMPATIBLE MATERIALS TO AVOID: Acids And Oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

HAZARDOUS DECOMPOSITION: Oxides of Carbon, Hydrochloric acid

SECTION SEVEN - ENVIRONMENTAL PROTECTION PROCEDURES**SPILL RESPONSE:**

Wear suitable protective equipment. Eliminate any ignition sources. Contain release by using an inert material such as sand or oil absorbent and/or eliminate the spill source, if this can be done without risk. Take up and containerize for proper disposal. Do not discharge into sanitary sewer or storm sewer. Comply with all federal, state and local regulations on reporting releases.

WASTE DISPOSAL METHOD: Dispose of in accordance with all Local, State, and Federal regulations.

SECTION EIGHT - SPECIAL PROTECTION INFORMATION

EYE PROTECTION: Safety Glasses or Goggles

SKIN PROTECTION: Rubber gloves.

RESPIRATORY PROTECTION: Not normally needed if used according to label directions.

VENTILATION RECOMMENDATION: Local Exhaust: Not normally indicated Special: Not necessary

Mechanical: Not normally indicated Other: Normal indoor ventilation.

OTHER PROTECTION: Long pants and sleeves. Consider an apron.

SECTION NINE - SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Keep away from ignition sources.

OTHER PRECAUTION: None.

SECTION TEN - TRANSPORTATION INFORMATION:

Exemptions found in 49 CFR 173 may be applied to actual shipments: below is for reference purpose only:

DOT SHIPPING NAME:

DOT HAZARD CLASS:

Compound Cleaning Liquid, Non-Hazardous

None

UN/NA IDENTIFICATION NUMBER:

U.S. & CANADA GROUND LABEL

AIR & INT. OCEAN LABEL

6.1, UN 2810 PG III

Non regulated except bulk shipments.

6.1 – POISON

ENVIRONMENTAL NOTES:

This mixture contains materials subject to section 313 (Sara) and to California proposition 65- possible carcinogen.

Perchloroethylene SARA III : **EPA Reporting Quantity: 100 LBS, DOT Reporting Quantity: 100 LBS**

DISCLAIMER OF LIABILITY

The manufacturer and seller warrant that the product conforms to its standard specifications when used according to directions. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product.

Information contained hereinafter is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material and the results to be obtained from the use thereof.

Footnotes:

NA-Not applicable

NE-data not established

CS-Cancer Suspect Agent

OX-Oxidizer ND-No data

Cor-Corrosive

CALC-Calculated

EST-Estimated

STEL-Short Time Exposure Limit

TLV-Threshold limit Value

PEL-Permissible Exposure Limit

TWA-Time Weighted Average, 8 hours

HMS, PPI-Hazardous Material Identification System, Personal Protection Index