

M A T E R I A L   S A F E T Y   D A T A   S H E E T      Rev 23200.04B

For Coating, Resins, and Related Materials NPCA 1-84

MANUFACTURER'S NAME  
BENJAMIN MOORE & Co.  
51 CHESTNUT RIDGE RD.  
MONTVALE, NJ 07645

EMERGENCY TELEPHONE NO.  
800-424-9300 (CHEMTREC)

DATE OF PREPARATION  
22-JAN-97 (Sup. 29-APR-91)

INFORMATION TELEPHONE  
201-573-9600

SECTION I - PRODUCT ID

PRODUCT CODE: 232	HMIS CODE	SARA TITLE 312
CLASS: WATER THINNED PAINT	Health: 1	Acute: NO
NAME: ENHANCE LATEX SEMI-GLOSS	Flammability: 0	Chronic: NO
ENAMEL	Reactivity: 0	Fire: NO
COLOR: ALL	Personal Prot.: B	Pressure: NO
		React: NO

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	MAX PCT	CAS NO. TLV	PEL	STEL	CEIL	MM Hg TEMP
Titanium Dioxide (f*)	17.5	13463677 10mg/m3	10mg/m3			N/A
C.I. Yellow (f*)	44.9	51274001 10mg/m3	10mg/m3			N/A
Hydrous Alum Silicates (f*)	5.1	1332587 10mg/m3	10mg/m3			N/A

f Federal Hazard List

\* Hazardous only as dust when product is sanded.

3 Sect. 313 of the Emergency Planning & Community Right-To-Know Act of 1986  
and of 40 CFR 37

This product may contain small amounts of materials known to the State of Cali  
cause cancer and reproductive harm.

SECTION III - PHYSICAL DATA

BOILING RANGE: N/A      VAPOR DENSITY: HEAVIER THAN AIR  
WEIGHT PER GAL: 9.2 - 10.1

EVAPORATION RATE: SLOWER THAN ETHER      % VOLATILE VOLUME: 69.0 - 72.4

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: NOT REGULATED FLASH PT.: >250 F PMCC  
LEL: Not Applicable

EXTINGUISHING MEDIA: FOAM      CO2      DRY CHEMICAL      WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may burst if exposed to  
extreme heat or fire. Toxic gases may form when product burns.

SPECIAL FIREFIGHTING PROCEDURES:

Cool exposed containers with water. Use self-contained breathing apparatus.


SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - ACUTE:

Inhalation - Irritation of the respiratory tract.

Skin and Eye Contact - Primary irritation.

Ingestion of large amounts could cause serious injury.



EFFECTS OF OVEREXPOSURE - CHRONIC: None Known

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

None expected when used in accordance with Safe Handling and Use Information (Section VIII).

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation - Remove to fresh air. Get medical help for any breathing difficulty. Eye Contact - Flush thoroughly with water. Call physician. Skin Contact - Wash with soap and water. Ingestion - Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Call physician.

SECTION VI - REACTIVITY DATA

STABILITY: STABLE HAZARDOUS POLYMERIZATION WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce carbon dioxide and carbon monoxide.

CONDITIONS TO AVOID: Elevated temperatures

INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Flush with water. Absorb with sawdust or rags.

WASTE DISPOSAL METHOD:

Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

VENTILATION:

Adequate to maintain working atmosphere below T.L.V. and L.E.L. (See Sect. II for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.

PROTECTIVE GLOVES: Waterproof during repeated contact.

EYE PROTECTION: Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES:

Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not throw or drop containers.

OTHER PRECAUTIONS:

Avoid contact with eyes and prolonged contact with skin or breathing of spray mist or sanding dust. Close container after each use. Keep out of reach of children. Do not take internally.

.....