# **SAFETY DATA SHEET**

B30W12650

# Section 1. Identification

Product name	: PROMAR® 200 Zero VOC Interior Latex Flat High Reflective White
Product code	: B30W12650
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: 1-800-474-3794 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

# Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Date of issue/Date of revision	: 9/20/2023 Date of previous issue : 6/14/2023 Version : 20 1/12

Date of Issue/Date	or revision	9/20/2023	Date of previous issue	: 0/14/2023	version	20
B30W12650	PROMAR® 200 Zero V High Reflective White	OC Interior Late	ex Flat		SHW-85-	NA-GHS-US

### Section 2. Hazards identification

Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Titanium Dioxide	≥10 - ≤25	13463-67-7
Calcium Carbonate	≤5	1317-65-3
Amorphous Silica	≤3	7631-86-9
Aluminum Hydroxide	≤3	21645-51-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acut	<u>e health effects</u>						
		: No known significant effects or critical hazards.					
		: No known significant effects or critical hazards.					
Skin contact	:	No known s	significant effects or critic	al hazards.			
Date of issue/Date	of revision	: 9/20/2023	Date of previous issue	: 6/14/2023	Version	: 20	2/12
	PROMAR® 200 Zero High Reflective White		itex Flat		SHW-85-	NA-GHS-US	\$

# Section 4. First aid measures

Ingestion	: No known significant effects or critical hazards.						
<u>Over-exposure signs/symp</u>	Over-exposure signs/symptoms						
Eye contact	: No specific data.						
Inhalation	: No specific data.						
Skin contact	: No specific data.						
Ingestion	: No specific data.						
Indication of immediate mee	dical attention and special treatment needed, if necessary						
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>						
Specific treatments	: No specific treatment.						
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.						

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protec	ive equipment and emergency procedures				
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.				
For emergency responders	: If specialized clothing is required to deal with the spillage, Section 8 on suitable and unsuitable materials. See also emergency personnel".	5			
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact and sewers. Inform the relevant authorities if the product pollution (sewers, waterways, soil or air).				
Date of issue/Date of revision	: 9/20/2023 Date of previous issue : 6/14/2023	Version : 20	3/12		
B30W12650 PROMAR® 200 Ze	ro VOC Interior Latex Flat	SHW-85-NA-GHS-US			

PROMAR® 200 Zero VOC Interior Late	ex Flat	SHW-85-NA-GHS-US
High Reflective White		

#### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling Protective measures

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

**Control parameters** 

#### **Occupational exposure limits (OSHA United States)**

Ingredient name		CAS #	Exposure limits	
Titanium Dioxide		13463-67-7	OSHA PEL (United States, 5/2 TWA: 15 mg/m <sup>3</sup> 8 hours. Forr ACGIH TLV (United States, 1/ TWA: 2.5 mg/m <sup>3</sup> 8 hours. For fraction, finescale particles	m: Total dust / <b>2023).</b>
Calcium Carbonate		1317-65-3	OSHA PEL (United States, 5/2 TWA: 5 mg/m <sup>3</sup> 8 hours. Form fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Forr NIOSH REL (United States, 10 [calcium carbonate]	: Respirable n: Total dust
Date of issue/Date of revision	on : 9/20/2023	Date of previous issue	: 6/14/2023 Version :	20 4/12
	R® 200 Zero VOC Interior La lective White	tex Flat	SHW-85-NA	A-GHS-US

# Section 8. Exposure controls/personal protection

		TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction TWA: 10 mg/m <sup>3</sup> 10 hours. Form: Total
Amorphous Silica	7631-86-9	NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS] TWA: 6 mg/m <sup>3</sup> 10 hours.
Aluminum Hydroxide	21645-51-2	ACGIH TLV (United States, 1/2023). [Aluminum, metal and insoluble compounds] TWA: 1 mg/m <sup>3</sup> 8 hours. Form: Respirable
		fraction

**Occupational exposure limits (Canada)** 

Ingredient name	CAS #	Exposure limits
None.		

#### **Occupational exposure limits (Mexico)**

	CAS #	Exposure limits
None.		

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate engineering controls Environmental exposure controls	<ul> <li>If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.</li> <li>Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment with the process equipment.</li> </ul>
	will be necessary to reduce emissions to acceptable levels.
Individual protection measure	<u>S</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	

# Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9.6
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.
Vapor pressure	: 2.3 kPa (17.5 mm Hg)
Relative vapor density	: 1 [Air = 1]
Relative density	: 1.38
Relative actionly	. 1.00

Media		Result	
cold water		Partially soluble	
Partition coefficient: n- octanol/water	: Not	applicable.	
Auto-ignition temperature	: Not available.		
Decomposition temperature	: Not	: Not available.	
Viscosity	: Kin	nematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)	
Molecular weight	: No	Not applicable.	
Heat of combustion	: 1.20	08 kJ/g	

Date of issue/Date	of revision	: 9/20/2023	Date of previous issue	: 6/14/2023	Version	:20	6/12
B30W12650	PROMAR® 200 Zero V High Reflective White	OC Interior Late	ex Flat		SHW-85-	NA-GHS-US	

### Section 10. Stability and reactivity

specific test data related to reactivity available for this product or its ingredients.
e product is stable.
der normal conditions of storage and use, hazardous reactions will not occur.
specific data.
specific data.
der normal conditions of storage and use, hazardous decomposition products should be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
Amorphous Silica	Eyes - Mild irritant	Rabbit	-	ug I 24 hours 25 mg	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-
Amorphous Silica	-	3	-

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Calcium Carbonate	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Date of issue/Date of revision	: 9/20/2023	Date of previous issue	: 6/14/2023	Version : 20	7/12
B30W12650 PROMAR® 200 High Reflective	) Zero VOC Interior La White	tex Flat		SHW-85-NA-GHS-US	

# Section 11. Toxicological information

Not available.

#### Aspiration hazard

Not available.

Information on the likely routes of exposure	:	Not available.
Potential acute health effect	:ts	
Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics						
Eye contact	: No specific data.					
Inhalation	: No specific data.					
Skin contact	: No specific data.					
Ingestion	: No specific data.					

#### Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	fects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

# Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Titanium Dioxide Amorphous Silica	Acute LC50 >1000000 μg/l Marine water Acute EC50 2.2 g/L Fresh water	Fish - <i>Fundulus heteroclitus</i> Daphnia - <i>Daphnia magna</i> - Neonate	96 hours 48 hours
	Chronic NOEC 12.5 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	: Not available.

**Other adverse effects** : No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
	/ision : 9/20/20 MAR® 200 Zero VOC Interi Reflective White		issue : 6/14/202		sion : 20 9/1 N-85-NA-GHS-US

Section 14. 1	Franspo	ort informatio	n		
Additional information	-	-	-	-	-
Special precautions	foruser	Multi-modal shinning		rovided for informat	ional purposes and do not
		consider container si mode of transport (s suitably for that mod to shipment, and cor of the person offering	izes. The presence ea, air, etc.), does r e of transport. All pa npliance with the ap g the product for tra ust be trained on all	of a shipping descu not indicate that the ackaging must be r oplicable regulation insport. People load of the risks derivin	ription for a particular product is packaged eviewed for suitability prior s is the sole responsibility
Transport in bulk ac to IMO instruments	cording :	Not available.			
		Proper shipping nan	ne : Not ava	ilable.	

### Section 15. Regulatory information

**TSCA 5(a)2 proposed significant new use rules**: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

#### <u>SARA 313</u>

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### International regulations

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### International lists

 sts
 : Australia inventory (AIIC): Not determined.

 China inventory (IECSC): Not determined.

 Japan inventory (CSCL): Not determined.

 Japan inventory (ISHL): Not determined.

 Korea inventory (KECI): Not determined.

 New Zealand Inventory of Chemicals (NZIoC): Not determined.

 Philippines inventory (PICCS): Not determined.

 Taiwan Chemical Substances Inventory (TCSI): Not determined.

 Thailand inventory: Not determined.

 Turkey inventory: Not determined.

 Vietnam inventory: Not determined.

# Section 16. Other information

#### Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Justification	
CARCINOGENICITY - Cat	Calculation method	
History		
Date of printing	: 9/20/2023	
Date of issue/Date of revision	: 9/20/2023	
Date of previous issue	: 6/14/2023	
Version	: 20	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification a IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeffi MARPOL = International Convention for the Prevention as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available SGG = Segregation Group UN = United Nations	cient of Pollution From Ships, 1973

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs

Date of issue/Date	of revision	: 9/20/2023	Date of previous issue	: 6/14/2023	Version	: 20	11/12
B30W12650	PROMAR® 200 Zero V High Reflective White	OC Interior Late	x Flat		SHW-85-	NA-GHS-US	

# Section 16. Other information

obtained from any other source.