## MATERIAL SAFETY DATA SHEET

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Royal Latex Tintable Interior / Exterior Primer

Product Code Identification Number: 175A340

MSDS Number:

GENERAL USE: Protective Coating

PRODUCT DESCRIPTION: Acrylic latex coating, slight ammonia odor



						-		
Stoddard solvent (Petroleum distillate, aliphatic)	8052-41-3	1 - 5	100	525	100	525		
Ethylene glycol (a,b,c)	107-21-1	1 - 5			39.4 C	127 C	Yes	500
2,2,4-trimethyl-1-1,3-pentanediol mono(2-methylpropanoate)	25265-77-4	1 - 5	no	ot establish	ed			
HAZARDOUS COMPONENTS	CAS#	(by weight)	PPM	MG/M3	PPM	MG/M3	TITLE III	LBS
HAZADDOLIS COMPONENTS	CAS#	%	OSHA PEL		ACGIH TWA		SARA	RQ
SECTIO	N 2 - HAZARDO	OUS INGI	REDIE	NTS				
Oak Brook, IL 60523-2100	USA	Infotrac (800) 535-5053 Outside USA (352) 323-3500						
(CITY, STATE AND ZIP CODE)	COUNTRY	EMERGENCY TELEPHONE NUMBER						
2200 Kensington Court		TELEPHONE NUMBER FOR INFORMATION (800) 311-8324						
Ace Hardware Corporation ADDRESS (NUMBER, STREET, P.O. BOX)		TELEDHON	E NI IMBI	ED EOD IN	IEODMA"	TION		
DISTRIBUTOR'S NAME								
Matteson, IL 60443-2800	USA	Infotrac (800) 535-5053 Outside USA (352) 323-3500						
(CITY, STATE AND ZIP CODE)	COUNTRY	EMERGENCY TELEPHONE NUMBER						
21901 South Central Avenue		(800) 311-	8324					
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHON						
MANUFACTURER'S NAME  Ace Hardware Paint Division		DATE PREPARED: May 2, 2006 SUPERSEDES: February 14, 2002 Page			of 4			

## SECTION 3 - HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

WARNING! Harmful or fatal if swallowed, harmful if inhaled or absorbed through the skin. May cause allergic skin reaction. May cause irritation to skin, eyes, and respiratory tract. Affects central nervous system Hazard symbols for this product - Not classified. Risk Phrases -Not classified

### POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.

EYES: High vapor concentration or contact may cause irritation and discomfort.

INGESTION: May result in vomiting; aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death. Large doses may be fatal.

CARCINOGENICITY No No

This product contains trace amounts of the following substances known to the state of California to cause cancer: 1,4 Dioxane, Ethylene Oxide, and Acetaldehyde.

NTP?

IARC MONOGRAPHS?

OSHA REGULATED?

#### MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Royal Latex Tintable Interior / Exterior Primer

May 2, 2006

## SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

## SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED)

FLAMMABLE LIMITS

LEL: Not applicable UEL: Not applicable

Non-flammable

**AUTOIGNITION TEMPERATURE:** 

Not determined

NFPA CLASS: None

GENERAL HAZARDS: Product is not considered flammable or combustible. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.

#### **EXTINGUISHING MEDIA**

Carbon dioxide, water, water fog, dry chemical, chemical foam

#### FIRE FIGHTING PROCEDURES

Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

None

#### HAZARDOUS COMBUSTION PRODUCTS

Smoke, fumes or vapors, oxides of carbon.

## SECTION 6 - ENVIRONMENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Small spills - wash to sanitary sewer with plenty of water. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to SARA Title III, Section 313 40 CFR 372, and CERCLA 40 CFR 302 for complete regulations concerning reporting requirements.

## SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **ENGINEERING CONTROLS**

The use of local exhaust ventilation is recommended. No other special controls are indicated.

#### PERSONAL PROTECTION:

RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits. NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

PROTECTIVE GLOVES: Neoprene, butyl or nitrile rubber gloves with cuffs.

EYE PROTECTION: Chemical safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash station nearby.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

Page 2 of 4

MATERIAL SAFETY DATA SHEET PRODUCT NAME: Royal Latex Tintable Interior / Exterior Primer Page 3 of 4 May 2, 2006 SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES VAPOR PRESSURE (MM Hg) VAPOR DENSITY (AIR = 1) 17 mm Hg @ 20° C SPECIFIC GRAVITY (WATER = 1) **EVAPORATION RATE (WATER = 1)** SOLUBILITY IN WATER FREEZING POINT Dispersible 32° F (0° C) APPEARANCE AND ODOR pН White viscous liquid, slight ammonia odor 9.0 - 9.5**BOILING POINT** PHYSICAL STATE 176°F (80°C) Liquid VISCOSITY (KREBS) 103 - 108 SECTION 10 - STABILITY AND REACTIVITY STABILITY UNSTABLE: CONDITIONS TO AVOID: STABLE: XXX Extreme temperatures, keep from freezing INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: CONDITIONS TO AVOID: None

WILL NOT OCCUR: XXX

SECTION 11 - TOXICOLOGICAL INFORMATION							
Hazardous Ingredients	CAS#	EINECS#	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)			
2,2,4-trimethyl-1-1,3-pentanediol mono(2-methylpropanoate)	25265-77-4	246-771-9	6860 mg / kg Oral - rat	Not established			
Ethylene glycol (a,b,c)	107-21-1	203-473-3	4700 mg / kg Oral - rat	10876 mg / kg Inhalation - rat			
Stoddard solvent (Petroleum distillate, aliphatic)	8052-41-3	232-489-3	> 5000 mg / kg Oral - rat	> 5500 mg / m3 / 4H Inhalation - rat			

## SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

## SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Product is classified as non hazardous, however, non-hazardous materials may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

## SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Not Regulated

DOT HAZARD CLASS / Pack Group: None / None

REFERENCE: Not Applicable

UN / NA IDENTIFICATION NUMBER: None

LABEL: None Required

HAZARD SYMBOLS: None

IATA HAZARD CLASS / Pack Group: None

IMDG HAZARD CLASS: None RID/ADR Dangerous Goods Code: None UN TDG Class / Pack Group: None

Hazard Identification Number (HIN): None

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes,

packaging materials and methods of shipping.

# MATERIAL SAFETY DATA SHEET PRODUCT NAME: Royal Latex Tintable Interior / Exterior Primer May 2, 2006 Page 4 of 4

## SECTION 15 - REGULATORY INFORMATION

#### TSCA (Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

#### SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories

Immediate health

#### 313 Reportable Ingredients:

(a) Indicates a toxic chemical subject to annual reporting requirements of Section 313 of SARA Title III of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

## CERCLA (Comprehensive Response Compensation and Liability Act)

(c) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24000 lbs) or greater amounts, according to 40 CFR 302.

#### California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

#### **CPR (Canadian Controlled Products Regulations)**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: Not controlled

## IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.

#### DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

#### EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

EC Risk Phrases Not classified	SYMBOL(S) REQUIRED FOR LABEL None	EC Safety Phrases S2 Keep out of the reach of children. S24/25 Avoid contact with skin and eyes			
SECTION	I 16 - OTHER INFOR	MATI	ON		
No specific notes.					
HMIS HAZARD RATINGS	HEALTH	1	* = Chronic Health Hazard	2 = MODERATE	
	FLAMMABILITY PHYSICAL HAZARD	0 0	0 = INSIGNIFICANT 1 = SLIGHT	3 = HIGH 4 = EXTREME	
REVISION SUMMARY:	This MSDS has been revised			4 - EXTINEIVIE	
NEVIOION SUIVIINANT.	Format revision	iii liie 10	nowing sections.		
MSDS Prepared by:	Comprehensive Data Base, In P.O. Box 5604 Lakeland, FL 33807 USA (863) 644 - 3298 www.com		ase.com		

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.