



Material Safety Data Sheet

The Sherwin-Williams Co.
101 Prospect Ave. N.W.
Cleveland, OH 44115


Emergency telephone number
Information telephone number
Date of preparation

001973 ✓
002916 002917 ✓
002917 001536 ✓
(216) 566-2917 ✓ 001937 ✓
(216) 566-2902
March 20, 1998
©1998, The Sherwin-Williams Co.

001536 ✓
002918 ✓
002916 ✓
002917 ✓
001837 ✓

Latex Interior Finishes - PROMAR® 200 / 400 Latex Interior Finishes

LI/4



- Base X ⇒
- Base Y ⇒
- Base Z ⇒
- Antique White ⇒
- Navajo White ⇒
- Dover White ⇒

		PROMAR® 200				PROMAR® 400		
		FLAT	EG-SHEL	SEMI-GLOSS	GLOSS	FLAT	EG-SHEL	SEMI-GLOSS
	Base X ⇒	B30 W 201	B20 W 201	B31 W 201	B21 W 201	B30 W 401	B20 W 401	B31 W 401
	Base Y ⇒	B30 W 202	B20 W 202	B31 W 202	B21 W 202	B30 W 402		B31 W 402
	Base Z ⇒	B30 W 203	B20 W 203	B31 W 203	B21 W 203	B30 W 403		B31 W 403
	Antique White ⇒	B30 W 204	B20 W 204	B31 W 204		B30 W 404	B20 W 404	B31 W 404
	Navajo White ⇒	B30 W 205	B20 W 205	B31 W 205		B30 W 405		B31 W 405
	Dover White ⇒	B30 W 206	B20 W 206	B31 W 206		B30 W 406	B20 W 406	B31 W 406
		B30 W 207 Luminous	B20 W 207 Luminous	B31 W 207 Luminous	B21 W 207 Luminous	B30 B 400 Black		
		B30 W 208 White						
			1 - 2	0 - 2	2 - 3		1	0 - 2
		<3% due to tinting	2 - 6	1 - 6	3 - 8	<3% due to tinting	2 - 5	1 - 4
		1 in Base Z only				1 in Base Z only		
		0.1 - 17 except White				5 - 13		
		1 Luminous only	0 - 0.1	0 - 0.1	0.1 except Base X	0 - 3		
			0 - 6			0 - 4		
		3 Luminous only						
		0 - 17	2 - 19	3 - 6 except Luminous		13 in Black only	9	0 - 6
		9 - 15	7 - 23	9 - 27	10 - 28	7 - 12 except Black	15	9 - 17
		0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2
		10.1 - 12.2	10.3 - 11.5	9.6 - 10.9	9.4 - 11.1	9.6 - 11.3	10.3 - 10.3	9.6 - 9.8
		40.2 - 52.8	38.0 - 51.9	40.3 - 55.8	36.5 - 50.1	49.3 - 69.2	53.9 - 54.0	55.4 - 55.8
		0.2	0.4 - 0.6	0.3 - 0.6	0.6 - 0.8	0.1 - 0.2	0.3	0.3
		0.4 - 0.7	1.1 - 1.2	0.7 - 1.2	1.3 - 1.6	0.4 - 0.7	1.0	0.7 - 0.8
		None / No	None / No	None / No	None / No	None / No	None / No	None
		1* - 0 - 0	2* - 0 - 0	2* - 0 - 0	2* - 0 - 0	2* - 0 - 0	2 - 0 - 0	2 - 0 - 0

P E R C E N T B Y W E I G H T

— Section 2 —

CAS No.	Hazardous Ingredients (percent by weight)	ACGIH TLV <STEL>	OSHA PEL <STEL>	Units	Vapor Pressure (mm Hg)
112-34-5	2-(2-Butoxyethoxy)-ethanol	Not Established			0.1
107-21-1	Ethylene Glycol	C 50	50	PPM	0.1
64742-54-7	Heavy Paraffinic Oil	5	5	Mg/M3 as Mist	
14808-60-7	Quartz	0.1	0.1	Mg/M3 as Resp. Dust	
14464-46-1	Cristobalite	0.05	0.05	Mg/M3 as Resp. Dust	
1332-58-7	Kaolin	2	5	Mg/M3 as Resp. Dust	
12001-26-2	Mica	3	3	Mg/M3 as Resp. Dust	
471-34-1	Calcium Carbonate	10	15[5]	Mg/M3 as Dust [Resp. Fraction]	
13463-67-7	Titanium Dioxide	10	10[5]	Mg/M3 as Dust [Resp. Fraction]	
1333-86-4	Carbon Black	3.5	3.5	Mg/M3	

* Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

→→→ MSDS Text Page Follows

37 07
04 08 10

Section 3 — Physical Data

PRODUCT WEIGHT See TABLE
 SPECIFIC GRAVITY 1.13-1.50
 BOILING RANGE 212-477 °F
 VOLATILE VOLUME 56-80 %
 pH 9.0-9.5

EVAPORATION RATE Slower than Ether
 VAPOR DENSITY Heavier than Air
 MELTING POINT N.A.
 SOLUBILITY IN WATER N.A.

Section 4 — Fire And Explosion Hazard Data

FLAMMABILITY CLASSIFICATION Not Applicable
 FLASH POINT See TABLE
 LEL N.Ap. UEL N.Ap.

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 5 — Health Hazard Data

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.

Section 6 — Reactivity Data

STABILITY — Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION — Will Not Occur

Section 7 — Spill Or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from these products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 8 — Protection Information

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3 (total dust), 3 mg./m3 (respirable fraction), OSHA PEL 15 mg./m3 (total dust), 5 mg./m3 (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 — Precautions

DOL STORAGE CATEGORY — Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Section 10 — Other Regulatory Information

CALIFORNIA PROPOSITION 65

WARNING: A20W81, A96W20, A96W22, A96W24, A97W40, A97W41, A97W42, A98W40, A98W41, A98W42, B21W201, B31W21, B31W22, B31W23, B31W27, B31W401, B31W404, B31W405 and B31W406 contain a chemical known to the State of California to cause cancer.

A21W71, A21W89, A22W41, (A21W40), A26W11, A26W12, A26W13, A26W14, A26W15, A26W17, A27W10, A27W11, A27W12, A27W13, A27W14, A27W15, A27W17, A29W40, A29W41, A29W42, A29W43, A86W14, A86W15, A86W16, A86W17, A87W40, A87W41, A87W42, A87W43, A88W14, A88W15, A88W16, A88W17, B20W201, B20W202, B20W203, B20W204, B20W205, B20W206, B20W207, B20W401, B20W404, B20W406, B21W202, B21W203, B21W207, (B28W700), B30B400, B30W201, B30W202, B30W203, B30W204, B30W205, B30W206, B30W207, B30W208, B30W401, B30W402, B30W403, B30W404, B30W405, B30W406, B30W700, B30W701, B30W702, B30W703, B31W201, B31W202, B31W203, B31W204, B31W205, B31W206, B31W207, B31W402, B31W403, B31W700, B31W701, B31W702, B31W703, Y38A102, Y38E105, Y38R104, Y38R106, Y38Y107 and Y38Y108 contain chemicals known to the State of California to cause cancer.

TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.